


C	OBJET SUBJECT		OBJET		SUBJECT
POMPE INCENDIE		FIRE FIGHTING PUT			
М	ODELE	MODEL			
	C	230			
DOC.	PI - 015	DATE	10-10-2017		

C30 (LIGHT ALLOY)





SPECIFICATIONS

Centrifugal type, two stages, multi-pressure

Output, low pressure: 3000 l/min @ 10 bar nominal condition at suction height 3m

Required power 100 kW abt. @ 3300 rpm

Output, high pressure: 400 l/min @ 40 bar nominal condition

Required power 100 kW abt. @ 3100 rpm

Automatic priming with liquid ring vacuum pump, priming within 30 seconds from 3,0 m suction height

Pressure relief valve on high pressure stage

Cleaner at high pressure inlet

Foam mixer "around the pump" -1%, 3% and 6%

Painting: red RAL 3000

Foam suction from tank or external source

DIMENSIONS & WEIGHT

mm 750 x 600 x 600 height

Dry weight, 120 kg Suction: DN 125 (5")

Suction. Div 123 (5)

Low pressure outlets 4 x Ø 2"1/2

High pressure outlet 2 x Ø 25 mm

MATERIALS

Case: light alloy / Impellers: bronze

Shaft material: stainless steel

Mechanical shaft seal

SAE 1410 transmission flange


Componente	POMPE INCENDIE VEHICULAIRE		Sheet
Item	TRUCK-MOUNTED FIRE-FIGHTING PUMP	10/10/17	1 of 1

N.B.: For information only. The manufacturer reserves the right to apply any change without any prior notification.



OBJET		SUBJECT			
POMPE INCENDIE		FIRE FIGHTING PUMP			
	MODELE		MODEL		
			C30		
	DOC.	PI - 015	DATE	10-10-2017	

C30 (LIGHT ALLOY)




Componente	POMPE INCENDIE VEHICULAIRE	Issued	Sheet
Item	TRUCK-MOUNTED FIRE-FIGHTING PUMP	10/10/17	1 of 1



OBJET		SUBJECT		
POMPE INCENDIE		FIRE FIGHTING PUMP		
MODELE		MODEL		
C30				
DOC. PI - 015 DATE 10-10		10-10-2017		

C30 (LIGHT ALLOY)




Componente	POMPE INCENDIE VEHICULAIRE	Issued	Sheet
Item	TRUCK-MOUNTED FIRE-FIGHTING PUMP	10/10/17	1 of 1



OBJET		SUBJECT		
POMPE INCENDIE		FIRE FIGHTING PUMP		
MODELE		MODEL		
C30				
DOC.	DOC. PI - 015 DATE 10-10		10-10-2017	

C30 (LIGHT ALLOY)




Componente	POMPE INCENDIE VEHICULAIRE	Issued	Sheet
Item	TRUCK-MOUNTED FIRE-FIGHTING PUMP	10/10/17	1 of 1



О	BJET	SUBJECT	
POMPE	INCENDIE	FIRE FI	GHTING PUMP
МС	DDELE	MODEL	
	C	230	
DOC.	PI - 015	DATE	10-10-2017

C30 (LIGHT ALLOY)





Pump Protection

Pump is equipped with pressure reduction valve and thermal relief valve

Control Panel

Control panel equipped with:

- Inlet pressure
- Outlet pressure normal and high, PTO engagement switch
- Operations hours
- Pump engagement indicator
- Pump overheat indicator
- Foam tank and water tank level indicator

Componente	POMPE INCENDIE VEHICULAIRE	Issued	Sheet
Item	TRUCK-MOUNTED FIRE-FIGHTING PUMP	10/10/17	1 of 2